## C Series Architectural Speakers

C 265



## Features

- 6-1/2" extended throw Kevlar woofer with phase plug, vented Strontium magnet, and dust screen
- I" aluminum dome tweeter utilizing dual chamber design for smoother response, and ferrofluid damping/cooling Three position level control for treble
- 12 dB/octave crossover network with premium parts24k gold "Constant Pressure" 10 AWG push terminalsKnockout plug for installing infrared receiver
- Acoustically transparent, fine mesh grill with paint shield Woven dust screen to protect woofer from in-wall debris
- Six-point "dog-leg" mounting system
- Optional NCK-6M New Construction Kit
- Parasound's 10 years parts, 5 years labor warranty

The **C 265** is the perfect in-wall speaker for filling your room with rich sound without the clutter of large box speakers. The 6.5" rigid Kevlar woofer gives tight, clean bass and the tweeter can be attenuated to adjust the sound to your liking. Whether it's background music or serious listening, the C 265 will bring your home, theater or office to life with uncompromising sound quality, virtually invisible installation and exceptional value. Enjoy!

## **Specifications**

Frequency response: 42Hz - 22kHz +/- 3dBNominal impedance:  $8\Omega$ Minimum impedance:  $6\Omega$ Sensitivity:  $88dB \mid watt/1 meter$ Power range: 10 - 80 watts Woofer size: 6-1/2" Woofer cone material: Kevlar Surround material: Butyl rubber Tweeter size/material: 1" aluminum dome Cut-out hole dimensions:  $7-3/8" \times 10-3/4"$ Outer edge of frame:  $8-5/8" \times 12"$ 



Parasound Products, Inc. 950 Battery Street, San Francisco, CA 94111 415-397-7100 / FAX 415-397-0144 www.parasound.com