



Architectural Speakers  
by Parasound


2007 Product Line

---

Parasound C-series is our line of inwall and ceiling speakers which deliver superior sound because our unswerving devotion is to performance and value, not cosmetic affectations.

### C-280 8" 2-way In-wall Speaker

10 year warranty



"The 8-inch woofer packed a pretty good punch, adding richness and authority."

—Home Theater

A kevlar woofer cone and dual-chamber aluminum dome tweeter assure detailed, natural sound. With no distortion at high listening levels and rich response at low volumes, the C-280 is ideal for both home theater excitement and casual background listening. Top-rated by reviewers.

- Mounting Depth: 3-1/2" (89 mm), front surface of wall or ceiling to back of the speaker
- Outer dimensions of bezel: 10" x 14" (254 mm x 356 mm)
- Frequency response: 36 Hz – 22 kHz, +/- 3 dB
- Power Range: 10 to 100 Watts
- Impedance, Nominal / Minimum: 8 ohms / 6 ohms
- Three-position level control for treble
- Optional NCK-8M New Construction Kit

### C-265 6-1/2" 2-way In-wall Speaker

10 year warranty



"This is a great-sounding speaker and a real value at its price point."

—Home Theater


Highest rating of 8 speakers tested by *Home Theater* magazine: **95 Performance; 96 Value**

We don't know of a better-sounding 6-1/2" inwall speaker. A kevlar woofer cone and dual-chamber aluminum dome tweeter make the C-265 your best choice when a C-280 is too large.

- Mounting Depth: 3" (76 mm), front surface of wall or ceiling to back of the speaker
- Outer dimensions of frame: 8-5/8" x 12" (219 mm x 305 mm)
- Frequency response: 42 Hz – 22 kHz, +/- 3 dB
- Power Range: 10 to 80 Watts
- Impedance, nominal / minimum: 8 ohms / 6 ohms
- Three-position level control for treble
- Optional NCK-6M New Construction Kit

### C-260 6-1/2" 2-way In-wall Speaker

10 year warranty



The C-260 is our model with the most "bang-for-the-buck" performance. Its polypropylene-mica woofer and fabric dome tweeter offer smooth, extended response and an appealing combination of sound and value.

- Mounting Depth: 2-7/8" (73 mm), front surface of wall or ceiling to back of the speaker
- Outer dimensions of frame: 8-5/8" x 12" (219 mm x 305 mm)
- Frequency response: 52 Hz – 20 kHz, +/- 3 dB
- Power Range: 10 to 70 Watts
- Impedance, nominal / minimum: 8 ohms / 6 ohms
- Optional NCK-6M New Construction Kit

With C-series you pay only for great sound,  
from the company with a legendary reputation for excellence.




### C-85 8" 2-way Ceiling Speaker

10 year warranty

The C-85 addresses the most common deficiency of ceiling speakers: thin, lifeless sound at typical moderate and background listening levels. The C-85 pumps out 50% more bass than a 6-1/2" speaker, yet it's nearly as inconspicuous when it's installed.

- Mounting Depth: 3-1/2" (89 mm), front surface of wall or ceiling to back of the speaker
- Outer diameter of frame: 10-3/4" (273 mm)
- Frequency response: 48 Hz – 22 kHz, +/- 3 dB
- Power Range: 10 to 80 Watts
- Impedance, nominal / minimum: 8 ohms / 6 ohms
- Pivoting 1" aluminum dome tweeter; foam absorption ring
- Optional NCK-8M New Construction Kit



### C-65 6-1/2" 2-way Ceiling Speaker

10 year warranty

There is a good reason why the C-65 is Parasound's best-selling speaker. The C-65 easily outperforms other 6-1/2" ceiling speakers, with clarity and bass extension that our competitors' 8" models can't match.

- Mounting Depth: 2-7/8" (73 mm), front surface of ceiling or wall to back of the speaker
- Outer diameter of frame: 9" (229 mm)
- Frequency response: 58 Hz – 22 kHz, +/- 3 dB
- Power Range: 10 to 70 Watts
- Impedance, nominal / minimum: 8 ohms / 6 ohms
- Pivoting 1" aluminum dome tweeter; foam absorption ring
- Optional NCK-3M New Construction Kit




### C-1002 10" 2 channel In-wall Subwoofer

10 year warranty

Add a C-1002 subwoofer to make your in-wall and ceiling speakers sound like large cabinet speakers. Its powerful, clean bass output assures deeper, fuller sound at every listening level. The C-1002 performs equally well even when it's mounted on the wall behind a piece of furniture, where it won't be seen.

- Mounting Depth: 3-1/2" (89 mm), front surface of wall or ceiling to back of the speaker
- Outer dimensions of frame: 12" x 12" (305 mm x 305 mm)
- Frequency response: 25 Hz – 120 Hz, +/- 4 dB
- Power Range: 10 – 100 watts, each channel
- Impedance, nominal / minimum: 8 ohms / 6 ohms, each channel
- Optional CX-1002, passive 120 Hz 2 channel crossover



CX 1002  
(sold separately)



---

We invite you to visit [www.parasound.com](http://www.parasound.com) for the most up-to-date information about Parasound and our extraordinary warranty. Read our product reviews and learn why Parasound is the undisputed leader for sound quality, dependability and lasting value.



*Premium full line electronics*



*Full line of high-value electronics*



*Half-rack space electronics*

---

© 2007 Parasound Products, Inc. Parasound reserves the right to change specifications, features and/or design without notice. Parasound and P logo are registered trademarks of Parasound Products, Inc. Rev # 1.0

PARASOUND

Parasound Products, Inc.  
950 Battery Street  
San Francisco, CA 94111